

ZPMV2.E47531 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component


See General Information for Wiring, Printed - Component

METAPLAST CIRCUITS LTD
 180 HYMUS RD
 SCARBOROUGH, ON M1L 2E1 CANADA

E47531

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Max		Meets C UL796 T UL96 I	C	Meets	C
	Min	Edge			Area Diam	Solder Limits	Oper Temp				
	mm(in)	mm(in)			mm(in)	C	sec	C			
Multilayer flexible materials interconnect constructions, Flammability Recognition only.											
4-2	-	-	-	DS	-	288	10	-	V-0	-	-
4-5	-	-	-	DS	-	288	10	-	VTM-0	-	-
Multilayer printed wiring boards.											
10-0	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:103	DS	101.6 (4.0)	274	10	130	V-0	All	-
10-1	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:102	DS	101.6 (4.0)	274	10	130	V-0	-	-
10-2 (Note1)	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:102	DS	101.6 (4.0)	260	20	130	V-0	All	-
10-3 (Note1)	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:17	DS	101.6 (4.0)	260	20	130	V-0	All	-
10-4 (Note1)	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:68	DS	101.6 (4.0)	260	20	130	V-0	All	-
10-5 (Note1)	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:102	DS	101.6 (4.0)	260	20	130	V-1	All	-
2-0	0.13 (0.005)	0.23 (0.009)	17.8 (0.70)	DS	50.8 (2.0)	288	3	105	V-0	-	-
3-0	0.1 (0.004)	0.23 (0.009)	17.8 (0.70)	DS	50.8 (2.0)	288	3	105	V-0	-	-
3-1	0.1 (0.004)	0.23 (0.009)	17.8 (0.70)	DS	50.8 (2.0)	288	3	105	V-1	-	-
6-0	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:137	DS	101.6 (4.0)	274	10	130	V-0	All	3
8-0	0.05 (0.002)	0.07 (0.003)	8.6 (0.34) Int:132	DS	101.6 (4.0)	274	10	130	V-0	All	2
Multilayer printed wiring, flammability rating only.											
4-0	-	-	-	DS	-	225	70	-	V-0	-	-
Multilayer rigid flex composite flexible materials interconnect constructions, Flammability Recognition only.											
4-3	-	-	-	DS	-	288	10	-	V-0	-	-

Single layer flexible materials interconnect constructions, Flammability Recognition only.											
4-1	-	-	-	DS	-	288	10	-	V-0	-	-
Single layer printed wiring boards.											
1-0	0.1 (0.004)	0.23 (0.009)	17.8 (0.70)	DS	50.8 (2.0)	288	3	105	V-0	-	-
5-0	0.05 (0.002)	0.05 (0.002)	9 (0.35)	DS	101.6 (4.0)	274	10	130	V-0	All	3
7-0	0.05 (0.002)	0.07 (0.003)	8.6 (0.34)	DS	101.6 (4.0)	274	10	130	V-0	All	2
9-0	0.05 (0.002)	0.05 (0.002)	9 (0.35)	DS	101.6 (4.0)	274	10	130	V-0	All	-

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2019-12-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"